

Canon

Delighting You Always

imageRUNNER
C3120

The New imageRUNNER C3120

ELEVATING QUALITY WITH SIMPLICITY

Seamless functionality, maximum performance



Business Can Be Simple

EASY & EFFICIENT

Designed with simplicity in mind, the imageRUNNER C3120 brings even greater workflow productivity and security by streamlining daily operations. With V² colour technology, standard wi-fi and Direct Access Point, enjoy quality colour prints with seamless connection.



V² COLOUR

Canon's V² colour imaging technology delivers outstanding colour quality. Be impressed with vivid and vibrant quality prints time after time.

USABILITY

APPLICATION LIBRARY

Use the application library for better work efficiency. Save time by making frequently performed operations or functions into an application that can be executed with a single button.

- **PRINT TEMPLATE**
Store frequently used form templates with predefined settings.
- **STANDBY SLIDE**
Display customised information on operation panel.
- **CONSUMABLES INFORMATION**
Keep track of toner levels at a glance.
- **SCAN TO PRESET DESTINATION**
Send scanned documents directly to a desired location.
- **ID Cards**
Perform a copy of an ID card on both sides conveniently.



SIMPLE, INTUITIVE NAVIGATION

Touch panel buttons, allowing home keys customisation and navigation through swipe and flick actions.



MULTIPLE PAPER SUPPORT

iR C3120 supports heavy paper printing. Heavy paper of up to 300g/m² (gsm) can be loaded in the multi-purpose tray. Foolscap/Folio, India Legal are also supported in Cassette 2, 3, 4 and MPT.



PRODUCTIVITY

Raise productivity with effective finishing accessories and paper handling capabilities.

SMALL SIZE PAPER SUPPORT

Small size originals such as A5 and A6 paper is supported, enabling the use of continuous scanning for small size paper that is high in demand at hotel, shops, medical institutions and regular offices.



SCAN TO EMAIL/FOLDERS

Increase productivity by scanning directly to email or folders. Supported file formats include JPEG, TIFF, compact and searchable PDF.



SMART SCAN

Scanned documents are rotated automatically with OCR, reducing the need for manual correction.



PLATEN COVER

Secure originals in position on the platen glass for scanning.



DUPLEX ADF

Scan double sided effortlessly without manually flipping paper.



INNER FINISHER

Collate, group and staple printouts. Supports ECO staple, staple-on-demand and standard stapling method.



SMART FEATURES

UNIFLOW ONLINE EXPRESS

Track and manage print, copy, scan and fax usage with usage reports. Optimise your prints through reporting and usage analytics.



MOBILE PRINTING

Canon Print Business app and a variety of mobile print service plugins such as, Canon Print Service, Google Cloud Print, AirPrint and Mopria Print Service are supported, enabling users to print from smart devices.



DIRECT CONNECTIVITY WITH MOBILE

The imageRUNNER C3120 comes with Direct Access Point capability. Print directly without requiring to be in the same network.



SPECIFICATIONS

Main Unit	
Machine type	A3 Colour Laser Multifunctional
Core functions	Print, Copy, Scan, Send and Optional Fax
Control Panel	12.7 cm (5 inch) TFT LCD WVGA Colour Touch panel
Memory	Standard: 2.0GB RAM
Storage	eMMC Standard: 2.0GB.
Interface Connection	NETWORK
	OTHERS
Paper supply capacity A4, 80g/m ² (gsm)	Standard: 1 200 Sheets 100-sheets Multi-purpose tray, 2 x 550-sheets Paper cassette Maximum: 2 300 Sheets (with Cassette Feeding Unit-AP1)
Paper output capacity A4, 80g/m ² (gsm)	Standard: 250 Sheets Maximum: 700 Sheets (with Inner Finisher-K1 and Copy Tray J2)
Supported media types	Multi-purpose Tray:
	Paper Cassette 1/2:
Supported media sizes	Multi-purpose Tray:
	Paper Cassette 1:
	Paper Cassette 2:
Supported media weights	Multi-purpose Tray:
	Paper Cassette 1/2 Duplex:
Warm-up Time	From Sleep Mode: 10s or Less From Power On: 19s or Less* * Time from device power on, until copy ready (not print reservation)
Dimensions (W x D x H)	565.0 x 664.0 x 880.0 mm
Installation Space(W x D)	1 141.0 x 1 117.0 mm * with Cassette open
Weight	Approx. 60.1kg without toner
Print specifications	
Print Speed (BW/CL)	Up to 20/20 pages/min (A4, A5, A5R, A6R), Up to 15/15 pages/min (A3)
Print Resolution	600 x 600dpi, 1200 x 1200dpi (half-speed)
Page description languages	Standard: UFR II Optional: PCL6, Adobe®PostScript®3™
Direct Print	Supported file types: PDF, EPS, TIFF/JPEG, XPS* * XPS is supported from LPR command print only.
Fonts	PCL fonts: 93 Roman, 10 Bitmap fonts, 2 OCR fonts, Barcode fonts* PS fonts: 136 Roman * Barcode Printing Kit-D1 is required
Operating System	UFR II: Windows® 7/8.1/10/Server2008/Server2008 R2/Server2012/Server2012 R2/Server2016/Server2019, Mac OS X(10.10 or later) PCL: Windows® 7/8.1/10/Server2008/Server2008 R2/Server2012/Server2012 R2/Server2016/Server2019 PS: Windows® 7/8.1/10/Server2008/Server2008 R2/Server2012/Server2012 R2/Server2016/Server2019, Mac OS X (10.10 or later) PPD: Windows® 7/8.1/10, MAC OS X (10.9 or later)
Copy Specifications	
Copy Speed (BW/CL)	Up to 20/20 pages/min (A4, A5, A5R, A6R), Up to 15/15 pages/min (A3)
First-Copy-Out Time (A4) (BW/CL)	Approx. 5.9s / 8.2s or less
Copy resolution	600 x 600dpi
Multiple Copies	Up to 999 copies
Copy Density	Automatic or Manual (9 Levels)
Magnification	Variable zoom: 25% - 400% (1% Increments) Preset reduction/enlargement: 25%, 50%, 61%, 70%, 81%, 86%, 100% (1:1), 115%, 122%, 141%, 200%, 400%
Scan Specifications	
Type	Optional: Colour Platen or Duplexing Automatic Document Feeder (DADF)
Document Feeder Paper Capacity 80g/m ² (gsm)	100 Sheets
Acceptable originals and weights	Platen: Sheet, Book, and 3-Dimensional objects Document Feeder media weight: 1-sided scanning: 38 to 128g/m ² (gsm) (BW), 64 to 128g/m ² (gsm) (CL) 2-sided scanning: 50 to 128g/m ² (gsm) (BW), 64 to 128g/m ² (gsm) (CL)
Supported media sizes	Platen: max. scanning size: 297.0 x 431.8 mm Document Feeder media size: A3, A4, A4R, A5, A5R, B4, B5, B5R, B6 Custom size: 128.0 x 139.7 mm to 297.0 x 431.8 mm
Scan Speed (BW/CL; A4)	1-sided Scanning: 55/55 images/min (300 x 300dpi, send), 30/30 images/min (600 x 600dpi, copy) 2-sided Scanning: 27.5/27.5 images/min (300 x 300dpi, send), 15/15 images/min (600 x 600dpi, copy)

Scan Resolution	Scan for Copy: up to 600 x 600dpi Scan for Fax: up to 600 x 600dpi
Pull Scan Specifications	ScanGear MF. For both TWAIN and WIA Supported OS: Windows® 7/8.1/10
Scan Method	PushScan, PullScan, Scan to Network, Scan to memory media (USB Memory Key), Scan to cloud-based services(uniFLOW)
Send Specifications	
Destination	Standard: E-mail/Internet FAX (SMTP), SMB, FTP Optional: Super G3 FAX
Address Book	LDAP (50)/Local (300)/One-touch(281)
Send resolution	Push: 300 x 300dpi (Email/SMB/FTP), 192 x 204dpi (IFAX) Pull: 50 x 50dpi, 75 x 75dpi, 150 x 150dpi, 200 x 200dpi, 300 x 300dpi, 400 x 400dpi, 600 x 600dpi
Communication protocol	FTP (TCP/IP), SMB (TCP/IP), SMTP
File Format	Standard: TIFF, JPEG ¹ , PDF(Compact, Searchable, Encrypted, Digital Signature) ¹ Single Page Only
Fax Specifications	
Maximum Number of Connection Lines	1
Modem Speed	Super G3: 33.6 kbps G3: 14.4 kbps
Compression Method	MH, MR, MMR, JBIG
Resolution	400 x 400dpi (Ultra Fine), 200 x 400dpi (Super Fine), 200 x 200dpi (Fine/Photo), 200 x 100dpi (Normal)
Sending/Receiving Size	Sending: A3, A4, A4R, A5 ² , A5R ² , B4, B5 ¹ , B5R ² Receiving: A3, A4, A4R, A5R, B4, B5, B5R ¹ Sent as B4 ² Sent as A4
FAX memory	Up to 512 pages
Speed dials	Max. 281
Group dials/destinations	Max. 299 dials
Sequential broadcast	Max. 310 addresses
Memory backup	Yes
Environmental Specifications	
Power source	220-240V 50/60Hz 10A
Power consumption	Maximum: Approx. 1 500W or less Standby: Approx. 34.3W ^{*1} Sleep mode: Approx. 2W ^{*2} , Approx. 1W ^{*3} ^{*1} Reference value: measured one unit ^{*2} Wireless LAN power save mode OFF ^{*3} Wireless LAN power save mode ON ^{*2-3} Sleep mode is not available in all circumstances due to certain settings.
Consumables	
Toner Yield (Estimated @ 5% Coverage)	NPG-67 TONER BK: 36 000 pages NPG-67 TONER C/M/Y: 19 000 pages
Paper Supply Options	
Cassette Feeding Unit-AP1	Paper Capacity:
	Paper Type:
	Paper Size:
	Custom Size:
	Paper Weight:
	Power Supply:
	Dimensions (W x D x H):
	Weight:
Output options	
Inner Finisher-K1	Tray Capacity (with 80g/m² (gsm) paper):
	Number of Trays:
	Lower Tray1:
	Upper Tray2:
	Paper Weight:
	Lower Tray1:
	Upper Tray2:
	Staple Position:
	Staple Capacity:
	Eco Staple:
	Staple On Demand:
	Power Supply:
	Dimensions (W x D x H):
Weight:	
Hardware Accessories	
PLATEN COVER-Y2, DADF-BA1, INNER 2WAY TRAY-J1, COPY TRAY-J2, MAIN BODY HTR-A, READER HEATER-L3, IC Card Reader Attachment-B2, COPY CARD READER-F1, COPY CARD READER ATTACHMENT-H3, UTILITY TRAY-B1, 3 Way Unit-D1, PS Printer Kit-CA1, PCL Printer Kit-CA1, BARCODE PRINTING KIT-D1, COPY CONTROL INTERFACE KIT-D1, NFC KIT-D1, SUPER G3 FAX BOARD-AV3, ADF ACCESS HANDLE-A1, STAPLE-P1	



To arrange for a demonstration, simply contact:

CANON INDIA PVT. LTD.

7th Floor, Tower B, Building #5, DLF Epitome Building, DLF Phase III, Gurugram-122002
Ph.: 0124-4160000 | Fax: 0124-4160011 | Web: in.canon

Disclaimer: This document is for information purpose only and the contents are subject to change without notice. Product options, name and availability may vary by regions. Nothing in this document should be construed as a warranty. We expressly disclaim any liability or contractual obligations with respect to this document. Canon and Business Can be Simple are trademarks of Canon Inc, and/or its affiliates. Other names may be the trademarks of their respective owners. uniFLOW, eCopy and Therefore are independent party software distributed by Canon Singapore Pte. Ltd.

DEALER'S STAMP