



High-Performance Wireless Ink Tank Printer for Small Businesses

The MAXIFY GX4070 makes your business look its best. Offering remarkable productivity for small work teams, this 4-in-1 inkjet printer provides ultra-affordable colour printing and a wide range of connectivity options.















2.7" TOUCH



CONNECTIVITY

HIGHLIGHTER & WATER RESISTANT PRINTS

The quick-drying pigment ink ensures high-quality document printouts that resist fading or moisture and accidental exposure to water.

EASY MAINTENANCE

The easy-to-replace maintenance cartridge makes maintenance fuss-free and extends printer lifespan even when printing in high volumes.

FULL NETWORK COMPATIBILITY

Wireless and Wired LAN connectivity enhances installation flexibility. Print wirelessly and connect to smart devices directly.

COMPACT, SPACE SAVING FOOTPRINT

The printer's compact footprint allows it to fit into tight spaces with ease.









| SPECIFICATIONS / MAXIFY GX4070 | | | | | | | |
|--------------------------------|--------------------------------------------------------------|----------------------------|--------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--|--|--|
| | Maximum Printing Resolution | | | 600 (horizontal) x 1,200 (vertical) dpi | | | |
| PRINT | Print Speed ⁻¹ (Mono/Colour) | ESAT/Simplex | | 18 / 13 ipm | | | |
| | | ESAT/Duplex | | 10 / 8 ipm | | | |
| | | FPOT Ready/Simplex | | 8/9 sec | | | |
| | Auto 2-Sided Printing (not applicable for Rear Flat Tray) | | | Yes | | | |
| CAN'2 | Scanner Type | | | Flatbed (ADF / Platen) | | | |
| | Scanning Method | | | Contact Image Sensor (CIS) | | | |
| | Optical Resolution ¹³ | | | 1,200 x 2,400 dpi | | | |
| | Maximum Document Size | Flatbed | | A4, LTR (216 x 297 mm) | | | |
| | | ADF | | A4, LTR, LGL | | | |
| | Copy Speed [™] | Colour | sFCOT/ Simplex | 17 sec | | | |
| ;0PY | | | sESAT/ Simplex | 11.1 ipm | | | |
| 2 | | ADF (Mono/ Colour) | ESAT/ Simplex | 15.2 / 7.4 ipm | | | |
| | Maximum Copies | | | 99 pages | | | |
| | Maximum Document Size | | | A4, LTR | | | |
| | Transmission Speed ¹⁵ | nission 5 Mono/Colour | | 3 sec / 1 min | | | |
| Ϋ́ | Transmission/Reception Memory*6 | | | 250 pages | | | |
| | PCFax | | | Windows: Available, Mac: Available | | | |
| | Automatic Dialing | Coded Speed Dialing (max.) | | 100 locations | | | |
| | | Group Dialing (max.) | | 99 locations | | | |
| | Maximum Input Capacity | Rear Tray | Plain Paper (64 g/m²) | Up to 100 sheets | | | |
| | | Cassette | Plain Paper (64 g/m²) | Up to 250 sheets | | | |
| | | Rear Flat Tray | Paperboard | 1 sheet | | | |
| | | ADF | Plain Paper (64 g/m²) | A4, LTR: 35 sheets, LGL: 5 sheets | | | |
| PAPER HANDLING | Media Size | Rear Tray | | A4, A5, A6, B5, LTR, LGL, Foolscap, FS, Envelope (COM10, DL, C5, Monarch), Card Size (91 x 55 mm), 4 x 6°, 5 x 7°, 7 x 10°, 8 x 10°, Square (127 x 127 mm), Custom (width. 89 - 216 mm, length: 127 - 1,200 mm) | | | |
| | | Cassette | | A4, A5, B5, LTR, Executive, Custom (width: 148 – 215.9 mm, length: 210 – 297 mm) | | | |
| | | Rear Flat Tray | | A4, B5, LTR, Custom (width: 89 – 215.9 mm, length: 127 – 1,200 mm) | | | |
| | | Auto 2-sided Printing | | A4, LTR | | | |
| | Media Type | Rear Tray | | Plain Paper (64 – 105 g/m²) High Resolution Paper (HR-101N) Hoto Paper Plus Glossy II (PP-201/PP-208) Glossy Photo Paper (GP-508) Photo Paper Plus Semi-Gloss (SG-201) Photo Paper Pot Luster (LU-101) Matte Photo Paper (MP-101) Double-Sided Matte Paper (MP-101D) Photo Stickers (PS-208/PS-808) Envelope | | | |
| | | Cassette | | Plain Paper (64 – 105 g/m²) | | | |
| | | | | | | | |

| NETWORK SYSTEM REQUIREMENTS & GENERAL SPECIFICATIONS | Operating System Compatibility | Please visit https://asia.canon to confirm OS compatibility and to download the latest drivers. | Windows 11 / 10 / 8.1 / 7 SP1 ⁷ macOS 10.14.16 – 12 or later Chrome OS | | | |
|------------------------------------------------------|--------------------------------------|-------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------|--|--|--|
| | Connectivity | Network | Wireless LAN IEEE802.11b/g/n/a ^{'8} /ac ^{'8} Wired LAN 100 Base-TX/10 Base-T | | | |
| | | Interface | USB 2.0 | | | |
| | Canon Printing Apps | Mobile | Canon PRINT Inkjet/SELPHY, Easy-PhotoPrint Editor, Creative Park | | | |
| | | Others | Easy Layout Editor, PosterArtist Lite, PosterArtist (Web), Canon Inkjet Smart Connect | | | |
| | Mobile/Cloud Printing Solutions | | AirPrint, Mopria, Canon Print Service (Android), Direct Wireless, MAXIFY Cloud Link | | | |
| | Power | | AC 100 – 240 V, 50/60 Hz | | | |
| | Power Consumption ¹⁹ | | 20 W (Standby: 0.9 W) | | | |
| | Duty Cycle | | Up to 33,000 pages/month | | | |
| | Recommended Monthly Print Volume | | 300 - 2,500 pages | | | |
| | Operation Panel | Display | 2.7" / 6.7 cm LCD (Touch Screen, Colour) | | | |
| | Dimensions (WxDxH) | Factory Configuration | 399 x 417 x 251 mm | | | |
| | | Output/ADF Trays Extended | 399 x 719 x 304 mm | | | |
| | Weight | | 9.5 kg | | | |
| CONSUMABLES | | Type/Colours | All Pigment Inks / Black, Cyan, Magenta, Yellow | | | |
| | Ink Bottles | Page Yield*10 | GI-76 PGBK: 6,000 (Standard) / 9,000 (Economy '') GI-76 PG C, M, Y: 14,000 ''2 (Standard) / 21,000 ''2 (Economy '') | | | |
| | User Replaceable | Maintenance Cartridge | MC-G03 | | | |
| Specifications are subject to change without notice. | | | | | | |

- Document print speeds are the averages of ESAT (Word, Excel, PDF) in Office Category Test for the default simplex mode, ISO/IEC 24734. Photo print speed is based on the default setting using ISO/JIS-SCID N2 on Photo Paper Plus Glossy II and does not take into account data processing time on host computer. Print speed may vary depending on system configuration, interface, software, document complexity, print mode, page coverage, type of paper used etc.
- ²² TWAIN driver (ScanGear) is based on the TWAIN specification V1.9 and requires the Data Source Manager comes with the operating system.
- Optical resolution is a measure of maximum hardware sampling resolution, based on ISO 14473 standard. Optical resolution scan is available, only when you use TWAIN Driver.
- ²⁴ Copy speeds are the average of sFCOT and sESAT, ISO/IEC 29183. Copy speeds (ADF) are ESAT of copy in sequence, ISO/IEC24735. Copy speed may vary depending on document complexity, copy mode, page coverage, type of paper used etc. and does not take into account warm up time.
- ^{'5} Black & white document fax transmission speed is based on default setting using ITU-T No. 1 chart. Colour document fax transmission speed is based on default setting using Canon Colour Fax Test Sheet. Actual transmission speed may vary depending on document complexity, fax settings at receiving end, and line conditions etc.
- ¹⁶ Page count is based on ITU-T No. 1 chart or Canon FAX Standard Chart No. 1.
- $^{^{\circ}7}$ Operation can only be guaranteed on a PC with a pre-installed Windows 7 or later.
- Wireless LAN IEEE802.11a/ac are available for Taiwan models only
- ^{'9} When copying ISO/JIS-SCID N2 (printed by inkjet printer) on A4 size plain paper using default settings.
- ¹⁰ Page yield is the estimated value based on Canon individual test method using the ISO/IEC 24712 colour chart continuous printing simulation with the Standard ink bottles after initial setup. Page yield varie significantly depending on contents printed and other factors. Package contains Standard Black ink bottle and Starter Cyan, Magenta and Yellow ink bottles
- The Economy mode reduces the ink consumption by lowering the density. More pages can be printed by using this mode
- 12 Based on 1 set of colour bottles.



Rear Flat Tray

SOUTH AND SOUTHEAST ASIA REGIONAL HEADQUARTERS CANON SINGAPORE PTE. LTD.

Paperboard (thickness: 0.1 - 0.7 mm)

1 Fusionopolis Place, #14-10 Galaxis, Singapore 138522 Tel: 65-6799-8888 | Fax: 65-6799-8882 | https://asia.canon

DEALER'S STAMP

This document is for information purpose only. The contents are subject to change without notice. Product options, name and availability may vary by regions. We expressly disclaim any liability or contractual obligations with respect to this document. Brands and product names are trademarks and/or registered trademarks of their respective owners.